

Coaxial Panel Connector 22_MMCX-50-0-4/111_O

Description

Straight bulkhead receptacle jack

Interface standards SUHNER-MMCX





Technical Data

Electrical Data		
Impedance	50 Ω	
Interface frequency max.	6 GHz	
Mechanical Data		
Number of matings	500	
Weight	0.0003 kg	
Environmental Data		
Operating temperature	-55 °C to 155 °C	
2011/65/EU (RoHS)	compliant	
Material Data		
Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	Gold Plating (without Nickel underplating)
Body	Brass	Gold Plating (without Nickel underplating)
Body Insulator	Brass PFA / PTFE	Gold Plating (without Nickel underplating)
		Gold Plating (without Nickel underplating)
Insulator		Gold Plating (without Nickel underplating)
Insulator Related Documents	PFA / PTFE	Gold Plating (without Nickel underplating)

Ordering Information

Bulk 100 pcs package

22_MMCX-50-0-4/111_OH

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.