

Coaxial Cable Connector 24_PC35-50-3-2/199_U

Description

Straight bulkhead cable feed through

Interface standards

IEC 60169-23

Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	26.5 GHz

Mechanical Data

Centre contact	soldered
Outer contact	soldered
Weight	0.0054 kg

Environmental Data

Operating temperature	-60 °C to 100 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	PS (Polystyrene)	
Gasket	VMQ (Silicone rubber)	
Fastening nut	Stainless Steel	
Washer	Bronze	SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00064426
Catalogue drawing	DCA-00089738
Assembly instruction	DOC-0000215467
Mounting hole	DOU-00008731

Ordering Information

Single package	24_PC35-50-3-2/199_UE
----------------	-----------------------

Additional Information

Suitable cables	EZ_141_TP_M17, EZ_141_AL_TP_M17, SUCOFORM_141, MULTIFLEX_141
-----------------	--