Data Sheet



Coaxial PCB Connector 82_QMA-50-0-3/111_N

Description

Straight PCB jack

Interface Standards

QMA QLF compliant



Technical Data

Electrical Data

 $\begin{array}{ll} \text{Impedance} & 50 \ \Omega \\ \text{Interface frequency max.} & 6 \ \text{GHz} \end{array}$

Mechanical Data

Board mounting type through holes Weight 0.0013 kg

Environmental Data

Operating temperature -40 °C to 85 °C 2011/65/EU (RoHS) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPRO Plating
Body	Brass	SUCOPRO Plating
Insulator	PFA / PTFE	

Related Documents

 Outline drawing
 DOU-00012676

 Catalogue drawing
 DCA-00012678

 Mounting hole
 DOU-00002524

Ordering Information

Bulk 100 pcs package 82_QMA-50-0-3/111_NH

Remarks

PCB connector with stand-offs

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.