

## Coaxial Cable Connector 21\_N-50-10-1/133\_U

### Description

Straight cable jack

Interface standards

IEC 61169-16\_MIL-STD-348A/304\_CECC 22210



### Technical Data

#### Electrical Data

Impedance	50 $\Omega$
Interface frequency max.	11 GHz

#### Mechanical Data

Centre contact	plugged
Outer contact	crimped
Weight	0.0381 kg

#### Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Crimp ferrule	Brass	SUCOPLATE (R) Plating

### Related Documents

Outline drawing	DOU-00007459
Catalogue drawing	DOU-00007461
Assembly instruction	DOC-0000343754

### Ordering Information

Bulk 50 pcs package	21_N-50-10-1/133_UF
---------------------	---------------------

### Additional Information

Suitable cables	S_10162_B-11, S_10172_B-11
-----------------	----------------------------