

## Coaxial Cable Connector 11\_BNC-75-3-38/133\_N

### Description

Straight cable plug

Interface standards

Interface compatible with IEC 61169-8



### Technical Data

#### Electrical Data

Impedance	75 Ω		
Interface frequency max.	4 GHz		
Frequency range	DC to 1 GHz	1 to 2 GHz	2 to 3 GHz
Return loss	30 dB	28 dB	26 dB

#### Mechanical Data

Centre contact	crimped
Outer contact	crimped

#### Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	SUCOPRO Plating
Outer contact	Bronze	SUCOPLATE (R) Plating
Body	Bronze	SUCOPLATE (R) Plating
Insulator	PTFE (Polytetrafluoroethylene)	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

### Related Documents

Outline drawing	DOU-00115943
Catalogue drawing	DCA-00006196
Assembly instruction	DOC-0000270344

### Ordering Information

Single package	11_BNC-75-3-38/133_NE
----------------	-----------------------

### Additional Information

### Remarks

for HDTV applications