

## Coaxial Cable Connector 14\_BMA-50-3-3/199\_N

### Description

Straight bulkhead cable plug

Interface standards

IEC 60169-33\_MIL-STD-348A/321



### Technical Data

#### Electrical Data

Impedance	50 Ω
Interface frequency max.	18 GHz

#### Mechanical Data

Centre contact	soldered
Outer contact	crimped
Weight	0.0037 kg

#### Environmental Data

Operating temperature	-65 °C to 125 °C
2011/65/EU (RoHS)	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium / Brass	Gold Plating (Nickel underplated)
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	PFA / PTFE	
Gasket	NR (Natural Rubber)	
Fastening nut	Stainless Steel	
Washer	Bronze	
Crimp ferrule	Brass	

### Related Documents

Catalogue drawing	DCA-00045259
Assembly instruction	DOC-0000185322
Mounting hole	DOU-00008972

### Ordering Information

Single package	14_BMA-50-3-3/199_NE
----------------	----------------------

### Additional Information

Suitable cables	RG_223_/U, ENVIROFLEX_142, RG_142_B/U
-----------------	---------------------------------------