

## Coaxial Cable Connector 24\_SMA-50-2-13/111\_N

### Description

Straight bulkhead cable feed through

Interface standards

IEC 60169-15\_MIL-STD-348A/310\_CECC 22110



### Technical Data

#### Electrical Data

Impedance 50 Ω  
 Interface frequency max. 18 GHz

#### Mechanical Data

Centre contact soldered  
 Outer 2contact crimped  
 Weight 0.0043 kg

#### Environmental Data

Operating temperature -65 °C to 165 °C  
 2011/65/EU (RoHS) compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium / Brass	Gold Plating (Nickel underplated)
Outer contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Body	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	
Gasket	VMQ (Silicone rubber)	
Fastening nut	Brass	
Washer	Bronze	
Crimp ferrule	Copper	

### Related Documents

Outline drawing DOU-00009108  
 Catalogue drawing DCA-00008868  
 Assembly instruction DOC-0000179078  
 Mounting hole DOU-00008748

### Ordering Information

Single package 24\_SMA-50-2-13/111\_NE  
 Bulk 100 pcs package 24\_SMA-50-2-13/111\_NH

### Additional Information

Suitable cables K\_02252\_D, ENVIROFLEX\_316\_D, G\_02232\_D