

Coaxial Cable Connector 16_SMA-R50-3-16/133_N

Description

Right angle cable plug

Interface standards

IEC 60169-15_MIL-STD-348A/310_CECC 22110

Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 18 GHz

Mechanical Data

Centre contact soldered
Outer contact crimped
Weight 0.0047 kg

Environmental Data

Operating temperature -65 °C to 165 °C
2011/65/EU (RoHS - including
2015/863 and 2017/2102) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PTFE (Polytetrafluoroethylene)	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

Related Documents

Outline drawing DPR-00185659
Catalogue drawing DCA-00183823
Assembly instruction DOC-0000368978

Ordering Information

Bulk 500 pcs package 16_SMA-R50-3-16/133_NP
Single package 16_SMA-R50-3-16/133_NE

Additional Information

Suitable cables RG_400_/U, ENVIROFLEX_400, ENVIROFLEX_142, RADOX_RF_400