

## Coaxial Cable Connector 16\_SMA-50-2-100/199\_N

### Description

Right angle cable plug

Interface standards  
SUHNER-SMA-26.5GHz



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 26.5 GHz

#### Mechanical Data

Centre contact plugged  
Outer contact soldered  
Weight 0.0056 kg

#### Environmental Data

Operating temperature -65 °C to 165 °C  
2011/65/EU (RoHS - including  
2015/863 and 2017/2102) compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Stainless Steel	Passivated (Plating)
Body	Stainless Steel	Passivated (Plating)
Insulator	PFA / PTFE	
Coupling nut	Stainless Steel	Passivated (Plating)

### Related Documents

Outline drawing DOU-00072798  
Catalogue drawing DCA-00006235  
Assembly instruction DOC-0000229425

### Ordering Information

Bulk 100 pcs package 16\_SMA-50-2-100/199\_NH

### Additional Information

Suitable cables EZ\_86\_TP\_M17, SUCOFORM\_86, MULTIFLEX\_86