

RF TERMINATION

Type 65_N-75-0-11/133_N

Description

Standard Termination, Low Power



Product Configuration

Connector	N plug (male)
Interface standards	IEC 60169-16_MIL-STD-348A/304_CECC 22210

Technical Data

Electrical Data

Nominal Impedance	75 Ω	
Frequency range	0 to 1.3 GHz	
Frequency sub range	DC to 1 GHz	1 to 1.3 GHz
VSWR max.	1.05	1.08
Power rating	1 Watt average power up to 30 °C ambient temperature, linearly derated to 0 Watt at 130 °C ambient temperature. 1500 Watt peak power	

Mechanical Data

Weight	0.044 kg
--------	----------

Environmental Data

Operating temperature	-40 °C to 130 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Part	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating

Ordering Information

Single Packaging	65_N-75-0-11/133_NE
Packaging	