

## Coaxial Cable Connector 24\_SMA-50-3-42/133\_N

### Description

Straight bulkhead cable feed through

Interface standards

IEC 60169-15\_MIL-STD-348A/310\_CECC 22110



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 18 GHz

#### Mechanical Data

Centre contact soldered  
Outer 2contact crimped  
Weight 0.0044 kg

#### Environmental Data

Operating temperature -65 °C to 165 °C  
2011/65/EU (RoHS) compliant

#### Material Data

| Piece Parts    | Material               | Surface Plating                   |
|----------------|------------------------|-----------------------------------|
| Centre contact | Copper Beryllium Alloy | Gold Plating (Nickel underplated) |
| Outer contact  | Brass                  | SUCOPLATE (R) Plating             |
| Body           | Brass                  | SUCOPLATE (R) Plating             |
| Insulator      | PFA / PTFE             |                                   |
| Fastening nut  | Brass                  |                                   |
| Washer         | Bronze                 |                                   |
| Crimp ferrule  | Copper                 |                                   |

### Related Documents

Outline drawing DOU-00009258  
Catalogue drawing DCA-00009259  
Assembly instruction DOC-0000184970  
Mounting hole DOU-00008748

### Ordering Information

Single package 24\_SMA-50-3-42/133\_NE

### Additional Information

Suitable cables RG\_223\_/U, ENVIROFLEX\_142, RG\_142\_B/U